

GLASS WALLS

DOUBLE GLAZING

Maintaining concentration in a workplace is important, whether private conversations & meetings, or perhaps a loud workplace environment, PC350 Double Glazed Walls provide a level of privacy and quiet that cultivates thought and promotes attention.

PC350 Double Glazing is the best option in sound control privacy, where open sight lines are maintained without compromise to design.

Find out how PC350 Double Glazed Walls can be an excellent option for your next project.

For more information please contact your PC350 Representative.

130 Nolan Court,
Markham, ON L3R 2V7
T: 905.475.6022
E: info@pc350.com

PC
350
ARCHITECTURAL
WALLS



BEAUTIFUL. ARCHITECTURAL. GLASS WALLS.

PC350.COM

GLASS WALLS

DOUBLE GLAZING 3/8" + 1/2" GLAZING

PC
350
ARCHITECTURAL
WALLS

Key Features:

- Modern Alternative to Drywall
- 3/8" or 1/2" Options
- Laminated Glazing provides higher values
- 5 Standard Colour Finishes
- Optional Finishes include any RAL number
- Integrates with Swing Door or Barn Door
- Similar profile design to Single Glazing
- Quick and simple to install
- Sleek and modern design
- Low profile Option

Key Benefits:

- Highest STC offerings
- Quieter working environment
- Visually appealing design
- Defines space while providing privacy
- Utilize the same profile as single glazing
- Consistent Design
- 7 Year warranty



For more information please contact your
PC350 Representative.

130 Nolan Court,
Markham, ON L3R 2V7
T: 905.475.6022
E: info@pc350.com

BEAUTIFUL. ARCHITECTURAL. GLASS WALLS.

PC350.COM

DOUBLE GLAZING

Understanding STC Ratings

For each increase or decrease of **5 STC points**, the perceived audible difference is increased or decreased by half.

STC output of PC350 Framing and Glass depend greatly on many project conditions, frequency of sound output and also surrounding physical construction.

There are many ways to help increase STC output, speak to your PC350 representative to find out how!

Glass Type (Double Glazed)	Glass S.T.C.
3/8" MONOLITHIC	44
3/8" WITH 0.030 LAMINATE	46
1/2" MONOLITHIC	47
1/2" WITH 0.030 LAMINATE	48
1/2" WITH 0.060 LAMINATE	49
1/2" WITH 0.090 LAMINATE	50

Ratings were achieved while testing using the following controls:

1. Fire stop caulking
2. Frames insulated with Roxul

For more information please contact your PC350 Representative.

130 Nolan Court,
Markham, ON L3R 2V7
T: 905.475.6022
E: info@pc350.com