

GLASS WALLS

SINGLE GLAZING

The single glazing line up consists of many profiles which make the final product.

Acting as a key design element in any space, glazed walls are sure to provide privacy while allowing uninterrupted lines of sight and flow of light.

Colour options from our standard five finishes, or Limitless with any RAL number.

Regardless of the application, many of our profiles will cross integrate. This results in a greater number of options and configurations to specify, making things easy.

For more information please contact your PC350 Representative.

130 Nolan Court,
Markham, ON L3R 2V7
T: 905.475.6022
E: info@pc350.com

BEAUTIFUL. ARCHITECTURAL. GLASS WALLS.

PC
350
ARCHITECTURAL
WALLS



PC350.COM

SINGLE GLAZING

Key Features:

- Accommodates all standard Partition sizes
- 1/4", 3/8" or 1/2" Glass Accommodation
- Unique profiles for Floor, Ceiling & Wall
- Pairs with Sliding Door, Barn Doors & Swing Doors
- Serves as Sidelight, Screen, Window or Clerestory
- Inspiring long spans can be achieved without mullions
- 5 Standard Colour Finishes
- Increased Height options

Key Benefits:

- Works with Vertical and Horizontal mullions
- Faceted Curved walls creating natural paths
- Spandrel options to personalize your space
- Slopped Walls provide further enhancement
- Various profile options to suit design intent
- Provides privacy
- Simple installation
- 7 Year Warranty



For more information please contact your
PC350 Representative.

130 Nolan Court,
Markham, ON L3R 2V7
T: 905.475.6022
E: info@pc350.com

SINGLE GLAZING

Understanding STC Ratings

For each increase or decrease of **5 STC points**, the perceived audible difference is increased or decreased by half.

STC output of PC350 Framing and Glass depend greatly on many project conditions, frequency of sound output and also surrounding physical construction.

There are many ways to help increase STC output, speak to your PC350 representative to find out how!

Glass Type (Single Glazed)	Glass S.T.C.
1/4" MONOLITHIC	32
3/8" MONOLITHIC	34
3/8" WITH 0.030 LAMINATE	36
1/2" MONOLITHIC	36
1/2" WITH 0.030 LAMINATE	38
1/2" WITH 0.060 LAMINATE	39

Ratings were achieved while testing using the following controls:

1. Fire stop caulking
2. Frames insulated with Roxul

For more information please contact your PC350 Representative.

130 Nolan Court,
Markham, ON L3R 2V7
T: 905.475.6022
E: info@pc350.com