

INLINE SLIDING DOOR

TOLERANCE

Ceiling heights from 82" (2083mm) to 120" (3048mm)

Base and ceiling frame

1 3/4" (44mm) frame & trim

Horizontal widths cut on site up to 120" (3048mm)

5 1/2" (140mm) top cover valance

DOOR OPTIONS

2" (51mm) Stile aluminum doors x 1 3/4" (44mm) thick

3 1/2" (89mm) Stile aluminum doors x 1 3/4" (44mm) thick

1 3/4" (44mm) wood doors

2" (51mm) wood doors

Aluminum doors can accommodate 1/4" (6mm), 3/8" (10mm) & 1" (25mm) sealed units

GLAZING OPTIONS

1/4" (6mm)

3/8" (10mm)

1/2" (12mm)

1" (25mm) Sealed Units

Laminate & tempered glass

Low iron

ACCOUSTICAL PROPERTIES

<i>Single Glazing</i>	<i>Glass S.T.C.</i>
1/4" (6mm)	32
1/4" (6mm) with 0.030	35
3/8" (10mm)	34
3/8" (10mm) with 0.030 laminate	35
1/2" (12mm)	36
1/2" (12mm) with 0.030 laminate	38
1/2" (12mm) with 0.060 laminate	39

SITE CONNECTIONS

Ceiling adjustment range +/- 3/4" (19mm)

Floor adjustment range +/- 1/2" (12mm)

Flush wall (wall start) +/- 1/2" (12mm)

Traditional wrap-around +/- 5/8" (16mm)

UNFINISHED WALL CONDITIONS

3 3/4" (95mm) walls - 2 1/2" (63mm) metal studs with 1 layer of 5/8" (16mm) gypsum wall board both sides

4 5/8" (117mm) walls - 3 5/8" (92mm) metal studs with 1 layer of 1/2" (12mm) gypsum wall board both sides

4 7/8" (124mm) walls - 3 5/8" (92mm) metal studs with 1 layer of 5/8" (16mm) gypsum wall board both sides

GLAZING OPTIONS SIDE LIGHTS

1/4" (6mm)

3/8" (10mm)

1/2" (12mm)

Laminate & tempered glass

Low Iron

ELECTRICAL

Room booking device wiring can easily be run through the frame



PC350
WE CREATE INSPIRED WORKSPACES