

## DOORS

Width between 33" (838mm) and 48" (1219mm)

Soft open/close system

Simultaneous sliding motion

Horizontal widths cut on site up to 144" (3658mm)

5 1/2" (140mm) top cover valance

Double VISTA opening width 172" (4369mm) minimum – 372" (9449mm) maximum

## GLAZING OPTIONS

Single glazing

Thickness: 1/4" (6mm), 3/8" (10mm), 1/2" (12mm)

Tempered or laminated glass

Specialty glass applications available on request

## ALUMINUM PROFILE DIMENSIONS

Slider top and bottom rail: 2 3/8" (60mm) H x 1 3/4" (44mm) W

Slider Stile: 2" (51mm)

Fixed Panel: 2" (51mm)

Valance: 4" (102mm)

Custom profile sizes

## AVAILABLE HARDWARE

Offset door pulls come in a variety of sizes, single or back-to-back

Recessed pulls

Floor locking door pulls

Accommodates a hook bolt lock for double VISTA

Flush wall (wall start) +/- 1/2" (12mm)

## SYSTEM REQUIREMENTS

Requires structural support to carry the weight of the system

Maximum slider weight: 265 lbs (120kg) per door

Maximum system height: 10' (3048mm)

Maximum bulkhead thickness is 7" (178mm) for 2-slider application and 9" (229mm) for 3-slider application

Maximum 3 doors on single VISTA and 6 doors on double VISTA application

## ACCOUSTICAL PROPERTIES

Single glazed STC assembly score ranges estimated to be: 32 – 35

## GASKETS

Available in black