

## DIMENSIONS & SIZING

Ceiling heights from 82" (2083 mm) to 120" (3048mm)

Framing components cut on site up to 120" (3048 mm)

2-3/4" (70 mm) high x 1-1/2" (38 mm) thick floor channel (narrow profile)

1-3/4" (44 mm) & 4" (101 mm) high floor channels (Elite profile)

3-1/4" (83 mm) high top valance / mounting rail

3-13/32" (87 mm) wide vertical aluminum door stile

## DOOR LEAF OFFERING

1-3/4" (44 mm) thick aluminum doors

1-3/4" (44 mm) thick wood doors (custom)

Single & Double Leaf

Brush Seal & Drop Seal

Locking & Non-Locking

Soft-close & Soft-open (w/ magnetic catch)

## DOOR LEAF GLAZING OPTIONS

3/8" (10 mm) & 1/2" (12 mm) Single glazing

Tempered & Laminated glass

Clear & Low Iron finishes

## SITE ACCOMMODATIONS

Glass - Floor adjustment of +/- 3/8" (10 mm) (narrow profile)

Door Leaf - Vertical adjustment of +/- 1/4" (6 mm)

## UNFINISHED WALL CONDITIONS

3-3/4" (95 mm) walls – 2-1/2" (63 mm) metal stud with 1 layer of 5/8" (16 mm) gypsum wall board both sides

3-1/2" (89 mm) walls – 2-1/2" (63 mm) metal stud with 1/2" (12 mm) layer of 5/8" (16 mm) gypsum wall board both sides

4-5/8" (117 mm) walls – 3-5/8" (92 mm) metal studs with 1 layer of 1/2" (12 mm) gypsum wall board both sides

4-7/8" (124 mm) walls – 3-5/8" (92 mm) metal studs with 1 layer of 5/8" (16 mm) gypsum wall board both sides

## ELECTRICAL

Room booking device wiring can be routed through door framing.

## WALL GLAZING OPTIONS

3/8" (10 mm) & 1/2" (12 mm) Single & Double glazing

Tempered & Laminated glass

Clear & Low Iron finishes