VISTA

DOORS

- Width between 33” (838mm) and 48” (1219mm)
- Soft open/close system
- Simultaneous sliding motion
- Horizontal widths cut on site up to 144” (3658mm)
- 5 1/2” (140mm) top cover valance
- Double VISTA opening width 172” (4369mm) minimum – 372” (9449mm) maximum

GLAZING OPTIONS

- Single glazing
- Thickness: 1/4” (6mm), 3/8” (10mm), 1/2" (12mm)
- Tempered or laminated glass
- Specialty glass applications available on request

ALUMINUM PROFILE DIMENSIONS

- Slider top and bottom rail: 2 3/8” (60mm) H x 1 3/4" (44mm) W
- Slider Stile: 2” (51mm)
- Fixed Panel: 2” (51mm)
- Valance: 4” (102mm)
- Custom profile sizes

AVAILABLE HARDWARE

- Offset door pulls come in a variety of sizes, single or back-to-back
- Recessed pulls – inside use only, for 90° applications
- Floor locking door pulls
- Accommodates a hook bolt lock for double VISTA
- Flush wall (wall start) +/- 1/2” (12mm)

SYSTEM REQUIREMENTS

- Requires structural support to carry the weight of the system
- Maximum slider weight: 265 lbs (120kg) per door
- Maximum system height: 10’ (3048mm)
- Maximum bulkhead thickness is 7” (178mm) for 2-slider application and 9” (229mm) for 3-slider application
- Maximum 3 doors on single VISTA and 6 doors on double VISTA application

ACCOUSTICAL PROPERTIES

- Single glazed STC assembly score ranges estimated to be: 32 – 35

GASKETS

- Available in black

PC350
WE CREATE INSPIRED WORKSPACES